

Models XB, XS, XH, XL - Stainless steel standard, ergonomic and bumper handles

## 1,200 LB CAPACITY



Model XB Shown

## 1,200 LB CAPACITY



Model XS Shown

## 1,200 LB CAPACITY



Model XH Shown

## 1,200 LB CAPACITY



Model XL Shown

### PRODUCT FEATURES:

- All welded construction (except casters).
- Stainless with premium #4 polished shelves in durable 16 gauge.
- 1-1/2" stainless corner angles, and stainless caster mounts.
- Bolt on casters, 2 swivel & 2 rigid, for superior tracking.
- Caster rigs available in steel or stainless for urethane wheels and steel only for full pneumatic wheels.
- Tubular handle with smooth radius bend - standard (XB), 4" raised ergonomic (XS), donut bumper at handle ends (XH), & 12" offset handle (XL).
- "L" shaped rubber bumpers on front legs standard on Model XH.
- 1-1/2" shelf lips up for retention except model XL (top shelf flush).
- Top shelf height - 35" except model XL - Top shelf height - 27" (Add 4" for N8 casters).
- Clearance between shelves - 25" except model XL - 17".

### OPTIONS:

- 2 wheel brakes on swivel casters - Brake Code.....Caster Type  
B5.....U5  
BX .....S5  
BN .....N8
- All swivel casters - Code AS
- Vinyl matting on top shelf - Code VM
- Flush top shelf (except XL) - Code FT
- Both shelves flush - Code FA
- Front leg "L" bumpers for Models XB, XL & XS - Code LB
- One side (length) lip down other three sides lips up (all shelves) (except XL) - Code LA
- Other shelf heights available - specify.
- Thermorubber casters available.
- Locking stainless drawer (16" w x 16" d x 4-1/4" h) with 2 keys - Code DZ

### MODEL XB - STANDARD HANDLE

WxL (in)	5" Urethane Casters Cat. No.'s			8" Casters Cat. No.'s	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Full Pneumatic	Wgt. (lbs)
18 x 24	XB124-U5	XB124-S5	52	-	-
30	XB130-U5	XB130-S5	56	XB130-N8	80
36	XB136-U5	XB136-S5	60	XB136-N8	84
24 x 36	XB236-U5	XB236-S5	70	XB236-N8	94
48	XB248-U5	XB248-S5	82	XB248-N8	106
30 x 48	XB348-U5	XB348-S5	94	XB348-N8	118
60	XB360-U5	XB360-S5	108	XB360-N8	132

### MODEL XS - ERGONOMIC HANDLE

WxL (in)	5" Urethane Casters Cat. No.'s			8" Casters Cat. No.'s	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Full Pneumatic	Wgt. (lbs)
18 x 24	XS124-U5	XS124-S5	48	-	-
30	XS130-U5	XS130-S5	54	XS130-N8	78
36	XS136-U5	XS136-S5	60	XS136-N8	84
24 x 36	XS236-U5	XS236-S5	70	XS236-N8	94
48	XS248-U5	XS248-S5	82	XS248-N8	106
30 x 48	XS348-U5	XS348-S5	94	XS348-N8	118
60	XS360-U5	XS360-S5	108	XS360-N8	132

### MODEL XH - DONUT BUMPER HANDLE

WxL (in)	5" Urethane Casters Cat. No.'s			8" Casters Cat. No.'s	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Full Pneumatic	Wgt. (lbs)
18 x 24	XH124-U5	XH124-S5	54	-	-
30	XH130-U5	XH130-S5	58	XH130-N8	82
36	XH136-U5	XH136-S5	62	XH136-N8	86
24 x 36	XH236-U5	XH236-S5	72	XH236-N8	96
48	XH248-U5	XH248-S5	84	XH248-N8	108
30 x 48	XH348-U5	XH348-S5	96	XH348-N8	120
60	XH360-U5	XH360-S5	110	XH360-N8	134

### MODEL XL - LOW PROFILE WITH RAISED OFFSET HANDLE

WxL (in)	5" Urethane Casters Cat. No.'s			8" Casters Cat. No.'s	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Full Pneumatic	Wgt. (lbs)
18 x 30	XL130-U5	XL130-S5	56	XL130-N8	80
36	XL136-U5	XL136-S5	60	XL136-N8	84
24 x 36	XL236-U5	XL236-S5	70	XL236-N8	94
48	XL248-U5	XL248-S5	82	XL248-N8	106
30 x 48	XL348-U5	XL348-S5	94	XL348-N8	118
60	XL360-U5	XL360-S5	108	XL360-N8	132