



Transport a compressed gas cylinder safely with durable hand truck featuring four wheels for easier, stable transport.



All hand trucks feature heavy floor plate with zero-lift height load.

Single Gas-Cylinder Hand Trucks

Safely load and transport heavy compressed gas cylinders

- Models available for cylinders from 6- to 12-in (155- to 305-mm) and 9- to 18-in (229- to 457-mm)
- Variety of wheel types available to suit a range of application and capacity needs, including pneumatic, semi-pneumatic and flat-free, for capacities up to 1,000-lb (454-kg)

Due to their weight, high-pressure contents, and unwieldy shape, industrial gas cylinders require a specially designed hand truck to minimize accidents and injuries. Constructed of 1-in (25-mm) and 1.25-in (32-mm) diameter steel tube with continuous welding, these hand trucks provides optimum safety, strength and longevity. Robust, v-shaped cylinder support cradles keep cylinder snug and secure, reducing cylinder rolling common in curved back designs. Durable, 1.5-in (38-mm) wide poly straps with steel cinch buckles, lab tested to 1138-lb (516-kg), secure cylinder to hand truck for safe transport.

Heavy-duty, 11-gauge (3-mm) floor plate with safety fins prevent warping or breaking. Features unique zero-lift height loading, allowing floor plate to lay flat, thereby eliminating the need to lift cylinder during loading and unloading.

Corrosion-resistant powder-coat finish throughout for long life and smooth handling.

Use models 35010 and 35012 to move larger propane or cryogenic cylinders.

Models 35004, 35006, and 35008 include wide-set dual 3-in (5-mm) swivel caster assemblies for easier, stable transport—fold flat for storage. Caster carriage features heavy steel bars and nylon washers for smooth folding action and easy storage in tight spaces.



Single Cylinder Hand Trucks

Max Cylinder Diameter in/mm	Wheel Type	Wheel Size in/mm	Rear Casters in/mm	Nominal Dimensions H x W x D	Straps per Cylinder	Weight Capacity lb/kg	Approv/Lstg Regulation	Model No	Ship Wt lb/kg
12/305	Semi-pneumatic	8/203	—	47 x 18 x 16 in 1194 x 457 x 406 mm	1	300/136	O, C, G, A	35000	34/15
12/305	Pneumatic	10.5/267	—	47 x 23 x 18 in 1194 x 584 x 457 mm	1	700/318		35002	38/17
12/305	Semi-pneumatic	8/203	3/76	47 x 18 x 16 in 1194 x 457 x 406 mm	1	700/318		35004	45/20
12/305	Pneumatic	10.5/267	3/76	47 x 21 x 19 in 1194 x 533 x 483 mm	1	1000/454		35006	48/22
12/305	Flat-free	10/254	3/76	47 x 21 x 19 in 1194 x 533 x 483 mm	1	1000/454		35008	48/22
18/457	Pneumatic	16/406	—	49 x 36 x 32 in 1245 x 914 x 813 mm	2	1000/454		35010	120/54
18/457	Flat-free	10/254	—	49 x 36 x 32 in 1245 x 914 x 813 mm	2	700/318		35012	120/54

1 Year
Limited Warranty